

Av. Camí Reial, 13-15
08184 PALAU-SOLITÀ I PLEGAMANS
BARCELONA (SPAIN)
Teléfono: 34 93 864 71 11 – Fax: 34 93 864 51 04
e-mail: chemicals@asutex.es
Website: www.asutex.es

TECHNICAL DATA SHEET**Updated: 26/01/15****Page: 1 de 1**

ASULAK E – BT

Elastic, colourable and covering lacquer (water based) for printing on garments

Dry and fix at room temperature. Very good fastnesses are obtained after 24 hours.

PVC, phthalates and APO free.

SCOPE OF APPLICATION

- Cotton and its blends
- PES, PA, lycra...
- It is colourable with ASUPRINT pigments (until 100 gr/kg)
- It allows print on conventional serigraphy systems and in automatic machines
- Excellent elasticity.
- It can be used 34/43 threats/cm² mesh
- Good covering action on dark backgrounds.
- Very good washing fastness

CHARACTERISTICS

Appearance:	Viscose paste
Colour	White
pH:	9 ± 0,5

APPLICATION

Print directly:

- a) Dry, fix to the air or predry with manual dryer and verify after 24 hours.
- b) Dry and curing in drying tunnel.

Wash the screens with water

For master clearing, add PRODER E – 695 NUEVO